



Sierra Wireless AirLink® Antenna: 4-in-1 BAT

AirLink® Antenna: 4-in-1 BAT

Efficient element design that assure high performance and robust communication link, BAT antenna is purposely designed for high-speed Telematics applications that can be mounted on any non conductive surface. The isolated dual 2G/3G/4G LTE antenna elements cover 698–960/1710–3800MHz and GNSS with dual-band Wi-Fi, and is supplied with low loss flame retardant cable.

| | | Specification |
|------------------------|----------------|--|
| PART NO. | | 6001201 |
| ELECTRICAL DATA | | |
| Frequency Range | Elements 1 & 2 | 698-960/1710-3800MHz |
| | Element 3 | 1562-1612MHz |
| | Element 4 | 2.4/5GHz |
| Operational Bands | Elements 1 & 2 | 2G/3G/4G LTE |
| | Elements 3 | GPS/GLONASS/Galileo/BeiDou |
| | Element 4 | 2.4/5GHz Wi-Fi |
| Peak gain: Isotropic¹ | Elements 1 & 2 | 2dBi (698-960MHz), 3dBi (1710-2170MHz), 5dBi (2500-3800MHz) |
| VSWR ² | Elements 1 & 2 | <2.5:1 |
| Isolation ² | | > 10dB |
| Pattern | | Omni-directional |
| Impedance | | 50Ω |
| Max Input Power | | 20W |
| GPS/GNSS DATA | | |
| Frequency Range | Element 3 | 1562-1612MHz |
| VSWR | | <2:1 ± 4MHz |
| Gain: LNA | ······· | 26dB |
| Polarisation | ··········· | Right Hand Circular |
| Operating Voltage | | 3-5V DC (fed via coax) |
| Current | | Typical <20mA |
| | | |

| | | Specification |
|-------------------|-------------|-----------------------------|
| MECHANICAL DATA | | |
| Dimensions | Height | 16.5mm (0.65") |
| | Length | 214mm (8.4") |
| | Width | 77mm (3.0") |
| Operating Temp | | -30° / +70°C (-30° / 158°F) |
| Material | | ASA |
| Colour | | Black |
| Weight | | 350g |
| MOUNTING DATA | | |
| Mounting Type | | Adhesive |
| CABLE DATA | | |
| Cell / LTE Cables | Cable | CS29 |
| | Length | 3m (10ft) |
| | Termination | SMA Plug |
| GPS Cable | Cable | RG174 |
| | Length | 3m (10ft) |
| | Termination | SMA Plug |
| Wi-Fi | Cable | CS32 |
| | Length | 3m (10ft) |
| | Termination | SMA Plug Reverse Polarity |

About Sierra Wireless

Sierra Wireless is building the Internet of Things with intelligent wireless solutions that empower organizations to innovate in the connected world. We offer the industry's most comprehensive portfolio of 2G, 3G, and 4G embedded modules and gateways, seamlessly integrated with our secure cloud and connectivity services. OEMs and enterprises worldwide trust our innovative solutions to get their connected products and services to market faster.

For more information, visit www.sierrawireless.com.



¹ Peak gain does not include cable attenuation ² VSWR & Isolation measured on 3mm thich ASA with 3m (10') of CS29 cable