





LTMG940

PRODUCT OVERVIEW

The LTMG940 is a 5-cable antenna with 4x LTE, NO WiFi and 1x GNSS. With 5-elements, the LTMG940 antenna provides a good match for the dual carrier modems that contain two pairs of LTE MIMO elements, one pair for each carrier. These fleet management systems offer Cellular carrier back-up.

The LTMG940 covers all Global Cellular & LTE frequencies. It also covers CBRS, Private LTE, and 5-G ready. GNSS operates on GPS, Galileo, Glonass, QZSS or Beidou.

Specify LTM940 for a model configured with GPS only.

Visit our eStore to customize an Antenna Online.

Electrical Specifications			
Frequency & Gain		694 - 960 MHz, 2 dBi 1710 - 3700 MHz, 5 dBi	
	GNSS Cable 5	1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi (RHCP)	
VSWR	LTE	< 2.5:1 VSWR over range (with 12" LMR-100)	
Impedance	50 Ohm Nominal		
Power Rating	10 Watts		
GNSS	Amplifier Bias Voltage	3 to 5 VDC	
	Gain	26 dB, 5 dBi Antenna	
	Current	20 mA max, 10 mA typical	

Mechanical Specifications			
Radome Material & Color	ASA UV-Inhibitive Plastic, Available in Black or White		
Radome Dimension	5.5" (13.9 cm) in diameter 2.38" (6.0 cm) in height		
1ft Pigtail Cables & Connectors Exiting Antenna	LTE	LMR-100 with SMA Plugs LTE-A (Green) & LTE-B (Red)	
	GNSS	RG-174 with SMA Plug (Yellow)	
Including 14ft Jumper Cables & Connectors	LTE	LL-195 with SMA Jack & SMA Plugs LTE-A (Green) & LTE-B (Red)	
	GNSS	RG-174 with SMA Jack & SMA Plug (Yellow)	
Operating Temperature	-40° to +80° C		
Mounting	7/8" Dia. Feed Through 3/4" Ig. Thread for up to 1/2" Thick Surface		
Shock & Vibration	IEEE1478, EN61373, MIL-810G, TIA 329.2-C		
Water Ingress	IP 67 (When Properly Mounted)		





MULTI-BAND ANTENNA

LTMG940-A3CB3C00G2C-WHT-180

LTE-A Cables LTE-B Cables NO WiFi
GNSS Color
Cable Length (in inches)

HIGHLIGHTS:

- Multiband: 4x LTE, NO WiFi, 1x GNSS
- Dual-Carrier MIMO
- Covers 694 3700 MHz
- 1 ft Cable Pigtails Exit Antenna; 14 ft Cable Jumpers Provided
- Color Coded Cable Type for EASY Match-Up
- Made-in-the-USA & UK

RELATED MODELS:

- LTMWG940
- (Wider Freq, Sub-6 & 5G Ready)
- LTMG944 (4x WiFi)
- LTMG943 (3x WiFi)
- LTMG942 (2x WiFi)
- LTMG941 (1x WiFi)
- LTM940 (GPS Model)

COMMON APPLICATIONS:

- Vehicle Fleet Management
- Multiband Modems
- Public Transportation

###USATaaa

By Phone: (919) 942-4214 By Email: info@usatcorp.com