



## SMW-410 multiband, 4-cable MIMO WiFi, & GPS

- 4 antennas in 1 antenna housing
- Covers GPS, WiFi 2.4/5.0 GHz, Military 4.4 or Public Safety 4.9 GHz
- Three WiFi elements can be used for WiFi MIMO or for separate WiFi modems

The SMW-410 Series Antennas features 4 elements in one antenna radome. The unique feature of this model is that it offers two identical high gain elements covering 2.4 GHz & 4.9-6.0 GHz. Of the remaining two elements in the SMW-410, one is used for GPS at 1575 MHz and the other covers 2.1-2.5 GHz & 4.4-6.0 GHz. All three elements offer an impressive 5 dBi gain.

This antenna is designed for applications that combine GPS with 2-cable or 3-cable MIMO WiFi, Public Safety at 4.9 GHz or Military at 4.4 GHz.

For the GPS interface, the antennas are outfitted with 15 feet (4.5 m) of RF-174 cable. The remaining three elements are fed with 15 feet (4.5 m) or low loss -195 cable.

The antenna is housed in an impact resistant radome made from ASA. It has been rated for shock and vibration as well as water ingress and will stand up to harsh weather or to rough treatment.

The antenna can be ordered as a surface mount antenna or as a mag-mount antenna.

**Model Configurator**

SMW-410-     -  -

Cable/Connector 1

Cable/Connector 2

Cable/Connector 3

Cable/Connector 4

Color

Cable Length in Inches (eg. 12 or 180)

Example: SMW-410-3C3C3C2C-WHT-180  
MGW-410-3C3C3C2C-BLK-180

Specify "SMWG" or "MGWG" instead of "SMW" or "MGW" for GPS/Glonass combination antenna.

Cable Options:		Connector Options:		Color Options:	
Code	Cable	Code	Connector	Code	Color
1	RG-58	A	TNC	WHT	White
2	RG-174	B	Mini UHF	BLK	Black
3	LL-195	C	SMA		
4	RG-188	D	SMB		
7	LMR-100	J	RP SMA		

(Other Configurations available.)

Specifications			
Frequency & Gain (peak):		Case Material:	White or Black UV resistant ASA
Cable 1	2.1-2.5 & 4.4-6.0 GHz, 5 dBi	Cable:	
Cable 2	2.4-2.5 & 4.9-6.0 GHz, 5 dBi	Cables 1 - 3	Separate LL-195 15 ft (4.5 m)
Cable 3	2.4-2.5 & 4.9-6.0 GHz, 5 dBi	Cable 4	RG-174, 15 ft (4.5 m)
Cable 4 (GPS)	1575.42 +/- 2 MHz, LNA: 26dB 5 dBi nominal RHCP	Connector:	SMA Plug (Male)
VSWR:	2:1 max over range	MGW Mounting:	Magnet Mount
Nominal Impedance:	50 Ohm	SMW Mounting:	Threaded metal stud 3/4" dia. x 1/2" long (1.9 cm x 1.3cm) for 1/4" (6 mm) thick metal; supplied with gasket & nut; other stud lengths available
Maximum Power:	10 Watts	Operating Temp:	-40° to +80° C
GPS		Shock & Vibration:	IEEE1478, EN 61373, MIL-810G, TIA 329.2-C
Amplifier Bias:	2.7 to 5 VDC	Dust/Water Ingress:	IP67
Noise Figure:	2.0 dB max, 1.7 dB typical		
Current:	20 mA max, 10 mA typical		
GPS & Glonass Option:	1575 MHz & 1602 MHz		
Case:	4.2"D x 3.2"H (10.7 cm x 8.1 cm) add 1/2" (1.3 cm) for mag base		



By Phone: (919) 942-4214  
By Email: info@usatcorp.com