



MultiTech OneBox[™] Smart Building

MultiTech OneBox[™] Smart Building kit simplifies the process of evaluating a LoRaWAN[®] network in a smart building application by including all the tools needed to report insights from multiple wireless LoRa[®] sensors.

Building owners and managers are focused on cost containment, compliance, sustainability and improved tenant experience. OneBox Smart Building brings together a targeted mix of LoRa-enabled MultiTech Reveal[™] sensors and an easy-to-deploy LoRaWAN network by including a pre-provisioned Conduit[®] AP access point. Paired with a fully integrated device management console to automate sensor provisioning and configuration and an intuitive dashboard to provide instant access to critical building information using customized data visualization and sensor notifications.

One box. One vendor. Value on day one.

BENEFITS

- Evaluate LoRaWAN performance in smart building applications
- Demonstrate return on investment prior to large-scale deployments
- Actionable sensor data in real time
- Simple scalability from a trusted vendor

FEATURES

- Quickly deploy and customize a LoRaWAN solution
- Monitor conditions using a variety of battery-powered LoRaWAN sensors
- Complimentary access to Device Management Console
- Cellular connectivity service included

www.multitech.com/onebox

REVEAL[™]

Get wise about your building.

MultiTech Reveal[™] sensors deliver critical asset information in real time so you understand exactly what's going on and can react quickly when needed.

Push Button Sensor



Water & Liquid Sensor



Movement Sensor



Door & Window Sensor



Air Temp & Humidity Sensor



What's in the OneBox™ Kit featuring Reveal™ Sensors



Reveal Sensor / Item

Description

Applications


Push Button Sensor



The single push button sensor can be used as a panic button, personal emergency response system (PERS), remote control, or other remote push button applications. When the button is pressed, an alert is sent to the wireless network.

- Silently alert security guards to emergencies or panic situations
- Install a Personal Emergency Response System (PERS) for seniors and healthcare facilities
- Use as a general remote control

Water & Liquid Sensor



The water leak sensor uses a water/liquid sensor probe to detect the presence of water or other liquids. When the presence of water or another liquid is detected, an alert is sent to the wireless network.

- Sump pump failure
- Plumbing fixture leaks
- Fuel leaks

Movement Sensor



The acceleration-based movement sensor uses an internal accelerometer to detect movement of an asset. When motion is detected that exceeds a certain threshold, an alert is sent over the wireless network.

- Asset protection and monitoring
- Building security
- Shock sensing
- General movement and acceleration sensing

Door & Window Sensor



The door/window sensor uses a magnet to detect open/close events for doors, windows, or other applications that use a magnet to detect close proximity.

- Monitor door and window activity
- Protect assets stored in cabinets and lock boxes
- Secure rooms and areas of the building

Air Temp & Humidity Sensor



The air temperature and humidity sensor uses air flow to measure temperature and humidity levels. If the temperature and/or humidity rises above or falls below the configured thresholds, an alert is sent over the wireless network.

- Monitor temperature and humidity levels
- Detect heating or cooling system failures
- Prevent condensation, mold, and odors in unconditioned areas

Conduit® AP Access Point



The MultiTech Conduit® AP access point conveniently provides deep in-building connectivity and improved performance for smart building applications.

- Collect data from wireless LoRaWAN sensors
- Forward sensor data to device management console using Ethernet or cellular connection
- Includes complimentary 90-day cellular data plan

Device Management Console



The free web-based device management console provides a fully integrated device management console for the automatic provisioning, monitoring, and configuration of sensors in the field. It also provides visualizations and advanced notification features that allow for full sensor-to-cloud solutions.

- Create charts and visualizations for your data
- Set up alerts and notifications
- Reconfigure sensors in the field

SENSOR SPECIFICATIONS OVERVIEW

Item / Type	Description				
Sensor Type	Push Button	Water & Liquid	Movement	Door & Window	Air Temp & Humidity
Part Number	RBS304-1-US	RBS301-WAT-US	RBS301-ABM-US	RBS301-DWS-US	RBS305-ATH-US
LoRa® Wireless					
Frequency Band (Mhz)	902-928				
Channel Plan	US915				
Protocol	LoRaWAN 1.0.2 compliant Class A & C				
Antenna	Internal				
Power					
Battery Powered	Yes				
Battery Type	1 X CR123				
User Replaceable	Yes				
Battery Life	200,000+ transmissions, 5-10 year depending on configuration				
Physical Description					
Physical Dimensions (LxWxH)	2.04 x 0.75 x 3.05 inches	1.46 x 0.75 x 2.81 inches	1.46 x 0.75 x 2.81 inches	1.46 x 0.75 x 2.81 inches	2.30 x 2.30 x 1.25 inches
Physical Weight	111g				
Enclosure Type	IP20 Plastic				
Mounting	Belt Clip, Lanyard or Wall Mount	Wall Mount (Screw or Adhesive)			
Environmental					
Operating Temperature	-30 to +70 °C				
Operating Humidity	0 - 90% (non-condensing)				
Storage Temperature	-40 to +100 °C				
Sensor Attributes					
Publish Type	Over-the-air configurable. Periodic, Threshold or Publish on change				
Periodic Interval	Over-the-air configurable from 1 minute to 127 hours				
Temperature Range	-	-	-	-	-40 to +100 °C
Temperature Accuracy	-	-	-	-	+/- 0.1°C
Humidity Range	-	-	-	-	0 - 100%
Humidity Accuracy	-	-	-	-	+/- 1.5 %RH
Acceleration	-	-	2g - 16g	-	-
Certifications					
Compliance	FCC Part 15				
Warranty	2-Years / www.multitech.com/legal/warranty				

Actual performance speeds may be affected by a variety of attributes such as cell tower distance, data loads, packet sizes, etc. See user guide for more information.

ORDERING INFORMATION

MultiTech OneBox

Model	Description	Region
MT1BX-915-BLD-KO	OneBox Smart Building. Includes 915 MHz, LTE Cat 1 mPower Programmable Access Point with five smart building sensors, external LoRa antenna, Ethernet cable, power supply and SIM card	North America

Contact USAT to Place an Order



USAT LLC
605 Eastowne Drive
Chapel Hill, NC 27514

Phone: (888) 550-8728
Email: info@usatcorp.com
Web: <https://usatcorp.com>

Services & Warranty

MultiTech's comprehensive Support Services programs offer a full array of options to suit your specific needs. These services are aimed at protecting your investment, extending the life of your solution or product, and reducing total cost of ownership. Our seasoned technical experts, with an average tenure of more than 10 years, can walk you through smooth installations, troubleshoot issues and help you with configurations.

Technical Support Services

At MultiTech, we're committed to providing you personalized attention and quality service while providing you a quick response to your product support needs. We have several options of support for you to choose from.

For additional information on Support Services as well as other service offerings, please contact your MultiTech representative or visit www.multitech.com/support.go

World Headquarters

Multi-Tech Systems, Inc.
2205 Woodale Drive
Mounds View, MN 55112 U.S.A.
Tel: +1 (763) 785-3500
Toll-Free: 800-328-9717
Email: sales@multitech.com
www.multitech.com

EMEA Headquarters

Multi-Tech Systems (EMEA)
Strata House
264-270 Bath Road
Harlington UB3 5JJ
United Kingdom
Tel: +(44) 118 959 7774
Email: sales@multitech.co.uk
www.multitech.co.uk



Features and specifications are subject to change without notice.

Trademarks and Registered Trademarks: MultiTech and the MultiTech logo, OneBox, Reveal: Multi-Tech Systems, Inc. All other products and technologies are the trademarks or registered trademarks of their respective holders.

2022-01 • 86002254 • © 2022 Multi-Tech Systems, Inc. All rights reserved.